



CHAPCOTM

CHAPCO[®] 808

Contact-Type (Spray) Adhesive

PRODUCT DATA

1. PRODUCT NAME

CHAPCO[®] 808 Contact-Type (Spray) Adhesive

2. MANUFACTURER

H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
800.552.6225 Office
800.952.2368 Fax
chapco-adhesive.com

3. DESCRIPTION

CHAPCO[®] 808 Contact-Type (Spray) Adhesive is tinted light blue for easy identification of where it is sprayed. It tacks quickly, has a web or lace spray pattern, and offers the user low soak-in with high bond strength. Designed for use by the professional contractor to bond a wide variety of construction surfaces including polyurethane insulation blocks, bead boards, insulation, carpet and carpet pad, polyethylene film, and sanding discs.

Packaging

One 20 Fl. Oz. aerosol can (591.4 mL)
Product #70-6523-5569

Coverage

Varies, depending on the porosity of the substrates.

Storage/Shelf Life

EXTREMELY FLAMMABLE. Do not store above 120°F or in direct sunlight. Maximum shelf life is 1 year from date of manufacture in unopened package.

Limitations

Not recommended for unsupported vinyl fabrics. Certain plastics and elastomeric substrates can exhibit bond failure due to plasticizer migration. Combinations of high temperatures and humidity can promote bond failure. For nonmetallic surfaces, test first for compatibility.

Cautions

EXTREMELY FLAMMABLE! For professional use only. Vapors will accumulate readily. Keep product away from heat, sparks, flames, and sources of static discharge. Do not puncture or incinerate empty container. Avoid contact with skin and eyes. Use directional arrow on spray head to avoid spraying in eyes. May cause eye, skin and respiratory tract irritation.

First Aid: In case of eye contact, flush with water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call a physician immediately. Harmful or fatal if swallowed. Do not induce vomiting. Call a physician immediately.

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about guidelines for the proper use and application of the covered CHAPCO products under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

4. TECHNICAL DATA

CHAPCO [®] 808 Contact-Type (Spray) Adhesive	
Base	Solvent
Consistency	Spray
Shelf Life	One Year, Unopened
Color	Light Blue
Weight per gallon	NA
Open Time	5-15 Minutes
VOC	600 g/L calculated

5. INSTALLATION INSTRUCTIONS

Preparation of Surfaces

Surfaces must be sound, dry and free from dirty, dust, old adhesives, grease, wax, or other foreign matter.

Application Instructions

Use with adequate ventilation. Overexposure to vapors may cause symptoms such as light-headedness, nausea, and headaches. Shake well before using. Point valve toward surface and spray from a distance of 8"–12" keeping the can moving to avoid a build-up on the surface. Let the adhesive dry to a tack before bonding together. For a permanent bond, spray both surfaces, allow to tack, then bond.

Clean-up

When dry, adhesive should rub off. Dried adhesive can be removed from carpet with mineral spirits or acetone. For dried adhesive film, use mineral spirits or acetone carefully, as these products can compromise the floor finishes. Always refer to the material manufacturer for proper dried adhesive removal procedures. Store indoors only. Should adhesive freeze, thaw at room temperature and stir well before using.

6. AVAILABILITY AND COST

To locate a distributor in your area, please contact:

phone: 800-832-9002
website: chapco-adhesive.com

7. WARRANTY

H.B. Fuller Construction Products Inc. offers a limited warranty on this product when installed in accordance with H.B. Fuller Construction Products Inc. printed specifications. Ask your sales associate or call 800-832-9002 for a copy of the limited warranty.

8. MAINTENANCE

Not applicable.

9. TECHNICAL ASSISTANCE

Information is available by calling the Technical Support Hotline:

Toll-free: 800-832-9023

Technical and Safety Literature:

To acquire Technical and safety literature, please call 800-832-9023.

CONTACT ADHESIVES



H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504
PH 800.832.9002
chapco-adhesive.com

808PDS-R1212-1