



CHAPCO

**PRODUCT
DATA**

SEAM ADHESIVES

CHAPCO® 29

Seam Sealer

1. PRODUCT NAME

CHAPCO® 29 Seam Sealer

2. MANUFACTURER

H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
800.552.6225 Office
800.952.2368 Fax
chapco-adhesive.com

3. DESCRIPTION

CHAPCO® 29 is a solvent based, flammable, carpet seam sealer specially formulated to prevent edge raveling and to seal the seams of most commercial and outdoor carpets; it is compatible with most carpet backings: ActionBac, Jute, Latex Unitary, Wovens, Rubber Backed, Urethane (Attached Cushion). It is fast setting and moisture proof. Excellent for both direct glue down and double bond applications. Not for use with PVC or vinyl backed products, vinyl sheet goods, or products where seam sealers are not required.

Product Features

- Superior bond
- For use with glue down and double bond installations

Packaging

One 8 Fl. Oz. bottle (236 mL)
Product #7065245969

One U.S. Quart bottle (945 mL)
Product #7065245169

Coverage

Approximately 160 lineal feet per 8 oz. bottle.
Approximately 640 lineal feet per quart bottle.

Storage/Shelf Life

FLAMMABLE! Do not store at temperatures above 120°F or in direct sunlight. Maximum shelf life is 1 year from date of manufacture in unopened package.

Limitations

Not for use with PVC or vinyl backed products, vinyl sheet goods, or products where seam sealers are not required.

Cautions

EXTREMELY FLAMMABLE! Use only in a well ventilated area. Do not use around sources of ignition such as open flames, pilot lights, etc. Do not incinerate container. Wrap the empty container and put it in trash collections. KEEP OUT OF THE REACH OF CHILDREN!

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about guidelines for the proper use and application of the covered CHAPCO® brand product(s) under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

4. TECHNICAL DATA

CHAPCO® 29 Seam Sealer	
Base	Solvent
Consistency	Medium Syrup
Shelf Life	One Year, Unopened
Color	Amber
Weight per gallon	Approximately 7.6 lbs
Open Time	20-30 Minutes
VOC	589 g/L Calculated

5. INSTALLATION INSTRUCTIONS

Preparation of Surfaces

None

Application Instructions

1. Apply a continuous bead of seam adhesive along one side of the trimmed edge where the face yarn enters the backing.
2. After applying the bead, butt both edges together while the adhesive is still wet.
3. Avoid contact with the nap of the carpet; clean excess sealer immediately with mineral spirits, use sparingly.

Clean-up

Safety solvent or mineral spirits.

6. AVAILABILITY AND COST

To locate a distributor in your area, please contact:

phone: 800-832-9002

website: chapco-adhesive.com

7. WARRANTY

H.B. Fuller Construction Products Inc. offers a limited warranty on this product when installed in accordance with H.B. Fuller Construction Products Inc. printed specifications. Ask your sales associate or call 800-832-9002 for a copy of the limited warranty.

8. MAINTENANCE

Not applicable.

9. TECHNICAL ASSISTANCE

Information is available by calling the Technical Support Hotline:

Toll-free: 800-832-9023

Technical and Safety Literature:

To acquire Technical and safety literature, please call 800-832-9023.



H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504
PH 800.832.9002
chapco-adhesive.com

29PDS-R1014-1