



CHAPCO® 305

Wall Carpet Adhesive

PRODUCT DATA

1. PRODUCT NAME

CHAPCO® 305 Wall Carpet Adhesive

2. MANUFACTURER

H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
800.552.6225 Office
800-832-9023 Technical Support
800.952.2368 Fax
www.chapco-adhesive.com

3. DESCRIPTION

CHAPCO® 305 Wall Carpet Adhesive has been formulated for the installation of carpet on interior wall. It provides the quick grab necessary for minimal slippage while providing ample working time for the installer. CHAPCO 305 may be used to install jute back, ActionBac® latex back, foam back, sponge back, and needle-punched carpet. **NOT RECOMMENDED FOR VINYL BACK OR VINYL FUSION BONDED CARPET.**

Packaging

Four U.S. Gallon pail (15.14 L)
Product #15035537

Coverage

Approximately 12-14 sq. yds. (108-126 sq. ft.) per gallon. Coverage will vary with the type of floor covering and job conditions.

Storage/Shelf Life

Store indoors only. Protect from freezing. Adhesive is freeze/thaw stable to 10°F. Prolonged or repeated freeze/thaw cycles should be avoided. Should adhesive freeze, allow to thaw at room temperature and stir well before using. Maximum shelf life is 1 year from date of manufacture in unopened package.

Limitations

Full cure takes 48-72 hours; the finished installation must be protected from moisture and/or freezing for a minimum of 24 hours. Not for use with vinyl back carpet.

Cautions

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about guidelines for the proper use and application of the covered CHAPCO products under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

4. TECHNICAL DATA

CHAPCO® 305 Wall Carpet Adhesive	
Base	Latex
Consistency	Medium Paste
Shelf Life	One Year, Unopened
Color	Off White
Weight per gallon	9.3 lbs.
Open Time	40-60 Minutes
VOC	>110 g/L

5. INSTALLATION INSTRUCTIONS

Preparation of Surfaces

Most normal interior walls provide an acceptable backing. Fill all holes, cracks, and indentations with a good quality patching compound. Walls must be clean, dry and free from dust and loose paint. Old wallpaper or other light weight decorative wall coverings should be removed. Old glossy or enameled surfaces should be roughened to provide a good bonding surface.

Application Instructions

The adhesive, carpeting, and room should be maintained at a minimum temperature of 65°F for 48 hours prior to, during, and after installation. For most backings use a 3/32" x 3/32" x 3/32" V-notched trowel. Some light weight carpets are thin and in order to prevent adhesive bleed-through spread the adhesive with a 1/16" notched trowel. Cut the carpet to properly fit the area being covered being sure to allow for trimming in corners and at the floor and ceiling. Place each piece of carpet into the adhesive within 30-40 minutes and apply pressure evenly from center to edge to remove trapped air. If seams are double-cut be sure adhesive is applied at seam area after cutting.

Clean-up

Fresh adhesive (and dried adhesive on resilient flooring) can be removed with a soapy, wet cloth.

6. AVAILABILITY

To locate a distributor in your area, please contact:

phone: 800-832-9002

website: www.chapco-adhesive.com

7. LIMITED WARRANTY

The product(s) covered by this Product Data Sheet are sold subject to a Limited Warranty and related terms. **H.B. Fuller Construction Products disclaims the implied warranties of merchantability and fitness for a particular purpose and all incidental and consequential damages arising out of the sale, purchase or use of this product.** For Limited Warranty details visit chapco-adhesive.com. To obtain a hard copy of the Limited Warranty call H.B. Fuller Construction Products at 800-832-9023 or mail a written request to the address in Section 2 of this Product Data Sheet.

8. MAINTENANCE

Not applicable.

9. TECHNICAL SERVICES

Technical and Safety Literature:

To acquire Technical and safety literature, please visit our website at chapco-adhesive.com.

SPECIALTY ADHESIVES



H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504
PH 800.832.9002
chapco-adhesive.com