



CHAPCO® Safe-Set® 7

Clear Thin Spread Adhesive



PRODUCT DATA

1. PRODUCT NAME

CHAPCO® Safe-Set® 7 Clear Thin Spread Adhesive

2. MANUFACTURER

H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
800.552.6225 Office
800-832-9023 Technical Support
800.952.2368 Fax
chapco-adhesive.com

3. DESCRIPTION

All CHAPCO® Safe-Set® adhesives are solvent-free, non-flammable, freeze/thaw stable, and nearly odor-free. Safe-Set adhesives can be used where other adhesives might present potential health risks. They are suitable for office buildings, hotels, hospitals, schools, restaurants, assisted living facilities, etc.

Safe-Set 7 is a pressure sensitive latex adhesive for the interior installation of vinyl composition tile and asphalt tile. When used according to directions, Safe-Set 7 will bond new tile to old floor coverings. The outstanding features of Safe-Set 7 are ease of application, immediate grab, and excellent moisture resistance. Safe-Set 7 dries to an transparent-clear film and is freeze/thaw stable. Not for use with solid vinyl tile.

Product Features

- High Moisture Technology - up to 90% RH/10 lbs. MVER
- ASTM F 2170 - 90% RH and ASTM F 1869 - HMT at 10 lbs.
- Formulated to provide immediate grab and quick-drying to expedite installations
- Provides the ability to bond new tile to old (tile-over-tile installation)
- Dries clear – allows chalk lines to remain visible during installation
- Extremely low-odor – ideal for use in occupied buildings
- LEED Compliant (VOC 0 g/L) and CRI Green Label Plus Certified

Packaging

One U.S. Gallon pail (3.7 L)
Product #15035592

Four U.S. Gallon pail (15.14 L)
Product #15035589

Coverage

Approximately 160-350 square feet per gallon. Coverage will vary with selection of trowel size.

Storage/Shelf Life

Store indoors only. Protect from freezing. Adhesive is freeze/thaw stable to 10° F. Prolonged or repeated freeze/thaw cycles should be avoided. Should adhesive freeze, thaw at room temperature and stir well before using. Maximum shelf life is 1 year from date of manufacture in unopened package.

Limitations

The finished installation must be protected from moisture and/or freezing for a minimum of 24 hours. Not for use with solid vinyl tile.

Cautions

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about guidelines for the proper use and application of the covered CHAPCO products under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

4. TECHNICAL DATA

CHAPCO® Safe-Set® 7 Clear Thin Spread Adhesive	
Base	Latex
Consistency	Thin Paste
Shelf Life	One Year, Unopened
Color	Off White-Wet Transparent Clear-Dry
Weight per gallon	9.2 lbs.
Open Time	1-72 Hours
VOC	0 g/L Calculated

5. INSTALLATION INSTRUCTIONS

Preparation of Surfaces

Use on grade, above grade, or below grade (if the floor covering is recommended for below grade installations). May be used over plywood, hardboard, concrete, terrazzo, steel, and well-bonded, wax-free floor coverings. Use a high quality latex-type patching compound to fill or level any irregular areas. The floor must be sound, dry, and free from dirt, dust, old adhesives, grease, wax, or other foreign matter. Painted or varnished surfaces must be sanded and dust-free. Concrete floors must be fully cured, free from dust, moisture, excessive alkalinity, curing agents, and excessive moisture vapor emissions up to 90% RH/10 lbs. MVER. On and below grade concrete must have a satisfactory moisture barrier beneath the slab. All dusting and very porous subfloors must be sealed. Sealer must be dry for 24-48 hours before application of adhesive. May be used to install tile over old cutback adhesive residue provided that the old adhesive ridges or puddling is removed and the floor is smooth.

All concrete substrates must be tested for moisture and pH prior to flooring installation. Install flooring with CHAPCO Safe-Set 7 over newly poured concrete, containing a vapor barrier with a moisture vapor emission rate up to 10 lb. per 1,000 sq. ft. (4.54 kg/ 93 m²) per 24 hours when tested in accordance with ASTM F 1869 or up to 90% RH when tested in accordance with ASTM F 2170. For concrete with greater moisture levels or with no vapor barrier, treat the concrete with CHAPCO'S DEFENDER™ Moisture Vapor Barrier. See Product Data Sheet for details. Test for pH in accordance with ASTM F 710. Range of 7-9 is required.

Application Instructions

The adhesive, tile, and room should be maintained at a minimum temperature of 65° F for 48 hours prior to, during, and after installation. Apply the adhesive with a 1/16" x 1/16" x 1/16" square notched (Porous); 1/16" x 1/32" x 5/64" U-notch (Porous & Non Porous), or a short nap roller. (Troweling is the preferred method and is recommended whenever the subfloor is very porous). Allow the adhesive to turn from white to an transparent-clear color before installing tile (approximately 30 minutes).



That set-up time will vary with the temperature, humidity, trowel selection and porosity of the subfloor. To test, touch the adhesive lightly; if it does not transfer to your finger, proceed with the installation. Tiles may be installed up to seventy-two (72) hours after the adhesive has dried (when using the 1/16" x 1/16" x 1/16" square notched trowel). Roll the entire floor with a 100 lb. roller within one (1) hour of installation. Restrict heavy foot traffic or rolling loads for at least 24 hours.

Clean-up

Fresh adhesive (and dried adhesive on resilient flooring) can be removed with a soapy, wet cloth. Dried adhesive can be removed from carpet with mineral spirits.

6. AVAILABILITY

To locate a distributor in your area, please contact:

phone: 800-832-9002

website: chapco-adhesive.com

7. LIMITED WARRANTY

The product(s) covered by this Product Data Sheet are sold subject to a Limited Warranty and related terms. **H.B. Fuller Construction Products disclaims the implied warranties of merchantability and fitness for a particular purpose and all incidental and consequential damages arising out of the sale, purchase or use of this product.** For Limited Warranty details visit chapco-adhesive.com. To obtain a hard copy of the Limited Warranty call H.B. Fuller Construction Products at 800-832-9023 or mail a written request to the address in Section 2 of this Product Data Sheet.

8. MAINTENANCE

Not applicable.

9. TECHNICAL SERVICES

Technical and Safety Literature:

To acquire Technical and safety literature, please visit our website at chapco-adhesive.com.



Conforms with LEED v4 low emitting interiors.
Compliant with (CDPH) Standard Method v1.2 VOC Emissions.

LEED® is a registered trademark of U.S. Green Building Council.

CHAPCO®, Safe-Set® and the CHAPCO® design are trademarks of H.B. Fuller Construction Products Inc.



H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504
PH 800.832.9002
chapco-adhesive.com

SS7PDS-R1120-20