



CHAPCO

**PRODUCT
DATA**

CHAPCO® 777

Liquid Latex Sealer

1. PRODUCT NAME

CHAPCO® 777 Liquid Latex Sealer

2. MANUFACTURER

H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504-6451 U.S.A.
800-552-6225 Office
www.chapco-adhesive.com

3. DESCRIPTION

CHAPCO 777 is a contract-grade liquid latex sealer, which provides enhanced adhesion and creates a suitable substrate for a variety of floor coverings. Ideal for interior substrates, such as concrete, gypcrete and wood surfaces.

Packaging

One U.S. gallon jug 6.4 LBS (4/case) (2.91 KG)
Product #70-4691-5069
Five U.S. gallon pail 32 LBS (14.51 KG)
Product #70-4691-1569

Recommended Substrates

- Concrete
- Gypcrete
- Wood

Coverage

Substrates	Coverage Rate* (square feet per gallon)
Concrete, Gypcrete and Wood Surfaces	300-400

* Substrate porosity conditions will determine exact coverages.

Storage/Shelf Life

Store in a cool dry area away from direct sunlight. Maximum shelf life is 18 months from date of manufacture in unopened container.

Limitations

CHAPCO 777 Liquid Latex Sealer cannot be used to reduce Moisture Vapor Emission Rate (MVER). For interior use only. Do not apply when the temperature is below 50° F (10° C).

Cautions

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about guidelines for the proper use and application of the covered CHAPCO products under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

4. TECHNICAL DATA

CHAPCO 777 Liquid Latex Sealer	
Base	Latex
Consistency	Thin, Pourable
Shelf Life	One year, unopened
Color	Wet: white Dry: Clear
Weight per gallon	6.42 lbs.
Open Time	2 Hours
VOC	0 g/L

5. INSTALLATION INSTRUCTIONS

Preparation of Surfaces

Surface must be structurally sound, clean and free from dust, dirt, paint, soap film, adhesive, grease, chemical curing compounds, and other foreign material.

Drying Time

1 hour

Application Instructions

To determine porosity of the surface, place dime size water drops of water on the substrate at several locations. If the water is absorbed into the surface within 30 seconds, the substrate is considered porous. If the water droplets dissipate immediately after placement, the substrate is considered excessively porous and CHAPCO 777 should be applied.

CHAPCO 777 Liquid Latex Sealer can be applied by brush, roller or spray. Spread CHAPCO 777 evenly across the surface in question, avoid pooling or puddling. Once the CHAPCO 777 is dry, repeat the porosity test to ensure acceptable porosity level are met. A second application may be needed, depending on the substrate condition.

Clean-up

Wash tools, hands and equipment with warm soapy water while material is still fresh.

6. AVAILABILITY AND COST

To locate a distributor in your area, please contact:

phone: 800-832-9002

website: www.chapco-adhesive.com

7. WARRANTY

H.B. Fuller Construction Products Inc. offers a limited warranty on this product when installed in accordance with H.B. Fuller Construction Products Inc. printed specifications. Ask your sales associate or call 800-832-9002 for a copy of the limited warranty.

8. MAINTENANCE

Not applicable.

9. TECHNICAL ASSISTANCE

Information is available by calling the Technical Support Hotline:

Toll-free: 800-832-9023

Technical and Safety Literature:

To acquire technical and safety literature, please call 800-832-9023

10. FILING SYSTEM

Division 3 - Concrete

Division 9 - Finishes

SURFACE PREPARATION



H.B. Fuller Construction Products Inc.
1105 South Frontenac Street
Aurora, IL 60504
PH 800.832.9002
www.chapco-adhesive.com



Environmentally Conscious
Manufacturer

777PDS-R1210-1